

 PORSCHE Technical Data	Macan			Macan 4			Macan 4S			Macan GTS			Macan Turbo		
	MY26 MSRP	\$80,300			\$84,000			\$89,900			\$105,300			\$112,700	
Motor															
Drivetrain	Rear Motor			Front & Rear Motor, ePTM			Front & Rear Motor, ePTM			Front & Rear Motor, ePTM			Front & Rear Motor, ePTM		
Motor type, front and rear	Permanent Magnet Synchronous			Permanent Magnet Synchronous			Permanent Magnet Synchronous			Permanent Magnet Synchronous			Permanent Magnet Synchronous		
Total maximum power, Launch Control, kW (hp)	265 (355)			300 (402)			380 (509)			420 (563)			470 (630)		
Total maximum torque, Launch Control (lb.-ft.)	415			479			604			704			833		
Total maximum power, kW (hp)	250 (335)			285 (382)			330 (442)			380 (509)			430 (576)		
Total maximum torque, (lb.-ft.)	415			479			578						811		
Pulse Inverter, front/rear (Amps)	NA/480			350/480			350/600			350/900			350/900		
Electric Motor diameter/length, Front (mm)				210/100			210/100			210/100			210/100		
Electric Motor diameter/length, Rear (mm)	210/200			210/200			230/150			230/210			230/210		
Power to weight ratio (lbs/hp)	14.1			13.1			10.4						8.6		
Batteries															
Cell type	Prismatic NMC			Prismatic NMC			Prismatic NMC			Prismatic NMC			Prismatic NMC		
Pack specification	100 kWh (Gross) 95 kWh (Net)			100 kWh (Gross) 95 kWh (Net)			100 kWh (Gross) 95 kWh (Net)			100 kWh (Gross) 95 kWh (Net)			100 kWh (Gross) 95 kWh (Net)		
Pack configuration	180 cells, 12 modules			180 cells, 12 modules			180 cells, 12 modules			180 cells, 12 modules			180 cells, 12 modules		
Pack weight (lbs)	1,329			1,329			1,329			1,329			1,329		
Chassis & Suspension															
Front axle	Aluminum Multi-link			Aluminum Multi-link			Aluminum Multi-link			Aluminum Multi-link			Aluminum Multi-link		
Rear axle	Aluminum Multi-link			Aluminum Multi-link			Aluminum Multi-link			Aluminum Multi-link			Aluminum Multi-link		
Steering system	electromechanical			electromechanical			electromechanical			electromechanical			electromechanical		
Steering ratio	14.2:1			14.2:1			14.2:1			14.2:1			14.2:1		
Turning circle diameter, w/o RAS, w/RAS (ft)	39.7/36.4			39.7/36.4			39.7/36.4			39.7/36.4			39.7/36.4		
Brakes & Wheels															
Caliper type	Aluminum Monobloc Fixed Calipers			Aluminum Monobloc Fixed Calipers			Aluminum Monobloc Fixed Calipers			Aluminum Monobloc Fixed Calipers			Aluminum Monobloc Fixed Calipers		
Rotor construction	Internally vented/Cast			Internally vented/Cast			Internally vented/Cast			Internally vented/Cast			Internally vented/Cast		
Caliper color	Black			Black			Red			Red			Red		
Number of pistons (front/rear)	4/4			4/4			6/4			6/4			6/4		
Rotor diameter (front/rear) mm	350/350			350/350			375/350			400/350			400/350		
Rotor thickness (front/rear) mm	33.9/29.9			33.9/29.9			35.9/29.9			37.9/29.9			37.9/29.9		
Maximum Regenerative Braking Force	200 kW			240 kW			240 kW			240 kW			240 kW		
Wheel size and design	20" Macan			20" Macan			20" Macan S			21" Macan Design			20" Macan Turbo		
Wheels: front/rear	20 x 7.5J ET32 20 x 10.0J ET49			20 x 7.5J ET32 20 x 10.0J ET49			20 x 7.5J ET32 20 x 10.0J ET49			21 x 8.5J ET27 21 x 10.5J ET47			20 x 7.5J ET32 20 x 10.0J ET49		
Tires: front/rear	235/55R20 285/45R20			235/55R20 285/45R20			235/55R20 285/45R20			255/45R21 295/40R21			235/55R20 285/45R20		
Standard tire type	All-Season			All-Season			All-Season			All-Season			All-Season		
Transmission															
Transmission type	Axially Parallel 3-shaft			Axially Parallel 3-shaft			Axially Parallel 3-shaft			Axially Parallel 3-shaft			Axially Parallel 3-shaft		
Ratio (Front/Rear)	9.8:1			9.2:1/9.8:1			9.2:1/10:1			9.2:1/9.0:1			9.2:1/9.0:1		
Dimensions, Aerodynamics, & Weight															
Length (inches)	188.35			188.35			188.35			189.2			188.35		
Wheelbase (inches)	113.9			113.9			113.9			113.9			113.9		
Width w/mirrors (inches)	84.7			84.7			84.7			84.7			84.7		
Width (inches)	76.3			76.3			76.3			76.9			76.3		
Height, normal level (inches)	63.8			63.8			63.8			63.8			63.8		
Track width front (inches)	66.4			66.4			66.4			66.4			66.4		
Track width rear (inches)	65.4			65.4			65.4			65.4			65.4		
Drag coefficient (Cd)	0.26			0.26			0.26			0.26			0.25		
Curb weight (lbs)	5,004			5,247			5,269			5,375			5,393		
Gross Vehicle Weight (lbs)	6,195			6,437			6,460			6,482			6,504		
Payload, maximum (lbs)	1,191			1,190			1,191			1,107			1,111		
Capabilities															
Towing, braked trailer (lbs)	4,409			5,512			5,512			5,512			5,512		
Towing, unbraked (lbs)	1,653			1,653			1,653			1,653			1,653		
Ground Clearance-low, normal, high level 2 (inches)	6.7	7.2	8.8	6.7	7.2	8.8	6.7	7.2	8.8				6.7	7.2	8.8
Approach/Departure-low, normal, high level 2(degrees)	11.6/19.4	12.6/20.7	15.2/23.9	11.6/19.4	12.6/20.6	15.2/23.9	11.6/19.4	12.6/20.6	15.2/23.9				11.6/19.4	12.6/20.6	15.2/23.9
	with tow hitch	11.6/19.3	12.8/20.2	15.2/22.9	11.6/19.3	12.6/20.3	15.2/22.9	11.6/19.3	12.6/20.3	15.2/22.9			11.6/19.3	12.6/20.3	15.2/22.9
Rampover angle: low, normal, high (degrees)	13.7	14.9	18.1	13.6	14.8	18	13.6	14.8	18				13.6	14.8	18
Cargo area volume (cu.-ft.) front trunk	2.9			2.9			2.9			2.9			2.9		
Cargo area volume (cu.-ft.) rear	18			18			18			15.8			15.8		
Cargo area volume (cu.-ft.) w/seats folded	46.5			46.5			46.5			44.4			44.4		
Performance															
Top track speed (mph)	136			136			149			155			161		
Acceleration 0-60 mph, w/Launch Control (sec)	5.4			4.9			3.9			3.6			3.1		
Acceleration 1/4 mile, w/Launch Control (sec)	13.9			13.5			12.3			12.0			11.4		
Charge Time, 0% - 100% SoC @ 9.6 kW (hrs)	11.0			11.0			11.0			11.0			11.0		
Charge Time, 10% - 80% SoC @ 270 kW (min)	21.0			21.0			21.0			21.0			21.0		
Fuel Economy/Rating*															
MPGe (combined, city/hwy)	99, 108/90			98, 106/89			91, 98/83						91, 99/84		
Range (miles)	315			308			288						288		

*US EPA estimates. Actual mileage will vary.

Pricing, specifications, technical data, performance statistics, and the availability of particular vehicles and options are subject to change without notice. Prices listed in this document are manufacturer's