

	911 Carrera T (992.2)	911 Carrera T Cabriolet (992.2)
Technical Data		
Engine		
Engine layout	Rear Engine	Rear Engine
Engine type	Boxer, twin-turbo	Boxer, twin-turbo
Cylinders	6	6
Valves per cylinder	4	4
Construction	Aluminum crankcase and heads	Aluminum crankcase and heads
Fuel Injection	Direct Fuel Injection (DFI)	Direct Fuel Injection (DFI)
Fuel	Premium	Premium
Displacement (Liters)	3.0 l	3.0 l
Bore/Stroke (mm/mm)	91.0 mm / 76.4 mm	91.0 mm / 76.4 mm
Maximum power output @ engine speed	388 hp @ 6500	388 hp @ 6500
Maximum torque @ engine speed	331 lb.-ft. @ 2000-5000	331 lb.-ft. @ 2000-5000
Maximum engine speed	7500	7500
Compression ratio (tolerance +/- 0.3)	10.2 : 1	10.2 : 1
Output per liter	126.3 hp	126.3 hp
Lubrication	Integrated dry-sump	Integrated dry-sump
Power to weight ratio (lb/hp) (PDK / manual)	8.5	9.0
Drivetrain	Rear-wheel drive	Rear-wheel drive
Chassis & Suspension		
Body	Monocoque lightweight body in a combination of steel, aluminum, and magnesium	Monocoque lightweight body in a combination of steel, aluminum, and magnesium
Front Axle	MacPherson strut with anti-roll bar	MacPherson strut with anti-roll bar
Rear Axle	Aluminum multi-link with anti-roll bar	Aluminum multi-link with anti-roll bar
Steering System	Variable ratio electronic, power steering	Variable ratio electronic, power steering
Steering Ratio	--	--
Steering Ratio with Rear-Axle Steering	14.1 : 1 (on-center) to 12.25 : 1	14.1 : 1 (on-center) to 12.25 : 1
Turning Circle	35.7 ft.	35.7 ft.
Brakes & Wheels		
Caliper type	Aluminum monobloc fixed-caliper brake	Aluminum monobloc fixed-caliper brake
Rotor material	Steel	Steel
Caliper color	Black	Black
Number of pistons (front/rear)	6 / 4	6 / 4
Rotor diameter (front/rear) mm	350 mm / 350 mm	350 mm / 350 mm
Rotor thickness (front/rear) mm	34 mm / 28 mm	34 mm / 28 mm
Standard wheel design	20" / 21" Carrera	20" / 21" Carrera
Standard wheel size (front/rear)	8.5J x 20" / 11.5J x 21"	8.5J x 20" / 11.5J x 21"
Standard tire size (front/rear)	245/35 ZR 20 / 305/30 ZR 21	245/35 ZR 20 / 305/30 ZR 21
Transmission		
Number of gears	6	6
Transmission type	6-speed manual	6-speed manual
Ratios		
1st	3.90	4.89
2nd	2.28	3.17
3rd	1.57	2.15
4th	1.18	1.56
5th	0.94	1.18
6th	0.78	0.94
7th	--	0.76
8th	--	0.61
Reverse	3.09	3.99
Rear Axle Ratio / rear constant transaxle ratio	3.39 / 0.92	3.39 / 0.92
Clutch 1/Clutch 2 diameter (inches)	9.0 inches	9.0 inches
Dimensions, Aerodynamics, & Weight		
Length (inches/mm)	178.8 in. / 4,542 mm	178.8 in. / 4,542 mm
Wheelbase (inches/mm)	96.5 in. / 2450 mm	96.5 in. / 2450 mm
Width w/ mirrors (inches/mm)	80.0 in. / 2033 mm	80.0 in. / 2033 mm
Width w/o mirrors (inches/mm)	72.9 in. / 1852 mm	72.9 in. / 1852 mm
Height with standard PASM suspension (inches/mm)	50.9 in. / 1293 mm	51.2 in. / 1,301 mm
Track width front (inches/mm)	63.1 in. / 1602 mm	63.1 in. / 1602 mm
Track width rear (inches/mm)	61.2 in. / 1555 mm	61.2 in. / 1555 mm
Cargo area volume (cu.-ft.) front trunk	132 l / 4.66 cu.-ft.	132 l / 4.66 cu.-ft.
Fuel tank capacity - refill volume (gal)	16.6 gal	16.6 gal
Curb weight (lbs)	3,316 lbs.	3,505 lbs.
Gross Vehicle Weight (lbs)	4,034 lbs.	4,376 lbs.
Payload range (lbs)	719 lbs.	871 lbs.
Performance		
Top track speed PDK (mph)	183 mph	182 mph
Acceleration 0-60 (sec)	4.3 sec.	4.5 sec.
Acceleration 0-60 PDK with Launch Control (sec)	--	--
Quarter mile time (sec)	12.7 sec.	12.9 sec.
Quarter mile time PDK with Launch Control (sec)	--	--
Fuel Economy/Rating		
Rating	-	-
City	TBD	TBD
Highway	TBD	TBD
Combined	TBD	TBD